

Maintenance Procedure for Kalingastone Engineered Quartz

Daily Maintenance

Wet mopping to be done by using Crystal Clean of Akemi / Stone & Tile Cleaner of DuPont / Equivalent (2 caps of Crystal Clean of Akemi in one bucket of water – 5 Litres).

The mop should be clean and wringed properly before applying at all the time. (Water should not drip from the mop)

The dirty mop should be cleaned in a separate bucket of water always before dipping in the bucket comprising Crystal Clean of Akemi/Equivalent Cleaner.

The Floor should be finally cleaned with plain water.

As & When Required

Deep cleaning to be done with a soft brush / White Buffing Pad using Crystal Clean of Akemi / Stone & Tile Cleaner of DuPont / Equivalent (2 caps of Crystal Clean / Stone & Tile cleaner in one bucket of water – 5 Litres).

Note : For deep / stubborn stains : Stone Cleaner of Akemi / DuPont's KlenzAll Cleaner / Equivalent (2 caps of Stone Cleaner of Akemi / KlenzAll of DuPont / Equivalent in one bucket of water – 5 Litres) to be used, if required.

Repeat cleaning the floor with plain water.

Vacuum the dirty water immediately.

Let the floor dry completely.

After ensuring proper cleaning, apply approximately ½ cup shining powder (Crystallization) of DuPont / Equivalent plus 1 cup clean water to stone surface.

Refinish using single disc machine fitted with White pad. Keep compound wet while refinishing with plenty of water. Add shining powder as needed.

Refinish area until the desired level of shine has been achieved.

Rinse well and use a wet vacuum until to remove all remaining compound.

Let the floor dry completely.