



Maintenance Procedure for Kalingastone Engineered Quartz

Daily Maintenance

- Wet mopping to be done by using Crystal Clean of Akemi / Stone & Tile Cleaner of DuPont / Equivalent (2 caps of Crystal Clean of Akemi in one bucket of water – 5 Litres).
- The mop should be clean and wringed properly before applying at all the time. (Water should not drip from the mop)
- The dirty mop should be cleaned in a separate bucket of water always before dipping in the bucket comprising Crystal Clean of Akemi/Equivalent Cleaner.
- The Floor should be finally cleaned with plain water.

As & When Required

- Deep cleaning to be done with a soft brush / White Buffing Pad using Crystal Clean of Akemi / Stone & Tile Cleaner of DuPont / Equivalent (2 caps of Crystal Clean / Stone & Tile cleaner in one bucket of water – 5 Litres).
 - Note : For deep / stubborn stains : Stone Cleaner of Akemi / DuPont'sKlenzAll Cleaner / Equivalent (2 caps of Stone Cleaner of Akemi / KlenzAll of DuPont / Equivalent in one bucket of water – 5 Litres) to be used, if required.
- Repeat cleaning the floor with plain water.
- Vacuum the dirty water immediately.
- Let the floor dry completely.
- After ensuring proper cleaning, apply approximately ½ cup shining powder (Crystallization) of DuPont / Equivalent plus 1 cup clean water to stone surface.
- Refinish using single disc machine fitted with White pad. Keep compound wet while refinishing with plenty of water. Add shining powder as needed.
- Refinish area until the desired level of shine has been achieved.
- Rinse well and use a wet vacuum until to remove all remaining compound.
- Let the floor dry completely.